



**German metal Surface treatment Chemicals Co.**  
**Research and Development Department.**  
**Detergent and disinfectants Division.**

# MATERIAL SAFETY DATA SHEET

## Biostar classic 300

### MULTIPURPOSE CLEANER

### QUAT DISINFECTION

#### MANUFACTURER:

German metal surface treatment (SUGEST)

P.O. Box 2951,Riyadh 11461,K.S.A.

Tel: (00966) (01) 4647711 (20 Lines)

Fax: (00966) (01) 2170866

### 1. Product and Company Identification

**NAME** Biostar classic 300  
**USE** Multipurpose cleaner disinfectant.  
**LABEL** Biostar classic 300  
**Company** German metal surface treatment chemicals co.

### 2. Product Description

**Biostar classic 300** is a highly effective synergetic blend of QUAT disinfectant agent for general purpose surface disinfectant.

### 3. Hazards Identification

#### Emergency Overview

-----

When used according to instructions, the product applicable to this MSDS is safe and presents no immediate or long-term health hazard. However, abnormal entry routes, such as gross ingestion, may require immediate medical attention.

#### Potential Health Effects

---

**HMIS:** Health 2 Flammability 3 Reactivity 0 Personal Protection None

**Eye Contact:** May cause eye irritation.  
**Skin Contact:** No irritation or reaction expected.  
**Inhalation:** Abnormal entry route  
**Ingestion:** May cause upset stomach, nausea (Abnormal entry route).  
**Carcinogenicity:** Not listed as a carcinogen by NTP, IARC, OSHA or ACGIH.

#### Physical

Substance highly flammable liquid and vapor.



**German metal Surface treatment Chemicals Co.**  
**Research and Development Department.**  
**Detergent and disinfectants Division.**

#### 4. Chemical Composition

Ingredient	CAS No	Percent
Isopropyl Alcohol	67 – 63 - 0	1 - 5
Benzalkonium chloride	8001 – 54 - 5	1 – 5
Nonionic surfactant	Property	1 - 5
Demineralized water	7732 – 18 - 5	To 100

#### 5. Physical and Chemical Properties

Appearance	Clear colored liquid
Odor	Fragrance
pH at 20 °C	4.5 – 5.5
Density g/cm <sup>3</sup> at 25 °C	0.970 to 1.1

#### 6. First Aid Measures

**Inhalation:**

Remove person to fresh air. If breathing is difficult, give oxygen and get medical attention.

**Skin contact:**

If irritation is experienced, flush with water. If irritation persists, get medical attention.

**Eye contact:**

In case of contact with the eyes, remove contact lenses if easy to do, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

**Ingestion:**

Seek medical advice. DO NOT induce vomiting unless directed to do so by medical personnel. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.

#### 7. Fire Fighting Measures

**Fire:** In a fire or if heated, a pressure increase will occur and the container may burst.

**Explosion:** This solution is not considered to be an explosion hazard.

**Fire Extinguishing Media:** water spray foam carbon dioxide (CO<sub>2</sub>) dry chemical.

**Special Information:** Although this product has a flash point below 200 Deg. F, it is an aqueous solution containing an alcohol and does not sustain combustion.

**Hazardous combustion products:**

Acid and heat accelerate decomposition.



**German metal Surface treatment Chemicals Co.**  
**Research and Development Department.**  
**Detergent and disinfectants Division.**

## 8. Accidental Release Measures

**Use personal protection recommended in Section 10 , isolate the hazard area and deny entry to unnecessary and unprotected personnel.**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

### **Environmental precautions:**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### **Clean-up methods:**

Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth. Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

## 9. Handling and Storage

### **Handling:**

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation.

### **Storage:**

**Storage Conditions:** Store in a cool, dry and good ventilated place. Keep container tightly closed after opening. Prevent direct sun light or ignition sources.

**Temperature Limit:** max 35 °C.

**Maximum Storage Period:** 24 Months under standard storage conditions.

**Container Type** Packaging must comply with requirements of Hazardous Substances (Packaging) Regulations 2001.

**For information on product shelf life, please review labels on container.**

## 10. Exposure Controls/Personal Protection

### **1- Propan-2-ol**

TWA: 983 STEL: 1230 (mg/m<sup>3</sup>) [Australia] TWA: 200 STEL: 400 (ppm) from ACGIH (TLV) [United States] [1999]  
 TWA: 980 STEL: 1225 (mg/m<sup>3</sup>) from NIOSH TWA: 400 STEL: 500 (ppm) from NIOSH TWA: 400 STEL: 500 (ppm)  
 [United Kingdom (UK)] TWA: 999 STEL: 1259 (mg/m<sup>3</sup>) [United Kingdom (UK)] TWA: 400 STEL: 500 (ppm) from  
 OSHA (PEL) [United States] TWA: 980 STEL: 1225 (mg/m<sup>3</sup>) from OSHA (PEL) [United States] Consult local  
 authorities for acceptable exposure limits.

### **Engineering controls:**

**Ventilation Requirements** provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. Supply sufficient replacement air to make up for air removed by exhaust systems.

Emergency shower and eyewash should be in close proximity.

**Respiratory protection:** None required.



**German metal Surface treatment Chemicals Co.**  
**Research and Development Department.**  
**Detergent and disinfectants Division.**

**Eye/face protection:** None required.  
**Skin protection:** No chemical protective gloves are required.

## 11. Stability and Reactivity

### Stability

Stable under normal use conditions.

**Conditions to Avoid:** keep away from open flame, hot sources and ignition sources

### Incompatibilities

Do not mix with strong acids, oxidizable materials.

### Reactivity Data

May develop static charge when poured and ignite vapors.

### Hazardous decomposition products:

Products may include oxides of carbon

### Hazardous Polymerization

Will not occur

## 12. Toxicological information

### Acute Toxicity

#### 1- Propan-2-ol

**Routes of Entry:** Absorbed through skin. Dermal contact. Eye contact. Inhalation.

#### Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.  
 Acute oral toxicity (LD50): 3600 mg/kg [Mouse]. Acute dermal toxicity (LD50): 12800 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 16000 8 hours [Rat].

#### Chronic Effects on Humans:

CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Development toxin [POSSIBLE]. May cause damage to the following organs: kidneys, liver, skin, central nervous system (CNS).

#### Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH [Glutaraldehyde].  
 MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. [Glutaraldehyde]. Mutagenic for bacteria and/or yeast. [Glutaraldehyde].

DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED][Glutaraldehyde]. Contains material which may cause damage to the following organs: blood, the reproductive system, liver, mucous membranes, spleen, central nervous system (CNS), Urinary system.

#### Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation (lung irritant, lung sensitizer). Slightly hazardous in case of skin contact (sensitizer, permeator).

#### Special Remarks on Toxicity to Animals:

Acute Toxicity: LD50 [Rabbit] dermal: Dose: 560 ul/kg. Reproductive Effects: TDL [male Rat] oral: Dose: 875 mg/kg given 35 days prior to mating TDL [female rat] oral: Dose 4370 mg/kg given 35 days prior to mating. (Glutaraldehyde)

#### 2- Benzalkonium Chloride

##### Routes of Entry

Absorbed through skin. Eye contact.

##### Toxicity to Animals



**German metal Surface treatment Chemicals Co.**  
**Research and Development Department.**  
**SUGEST Detergent and disinfectants Division.**

Acute Dermal LD50 Rat: 1420 mg/kg  
 Acute Inhalation LC50 Rat: 53 mg/m<sup>3</sup> 4 hours  
 Acute Oral LD50 Mouse: 150 mg/kg  
 Acute Oral LD50 Rat: 240 mg/kg

**Carcinogenicity**

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**Ecotoxicity:**

**1- Benzalkonium chloride**

LC50 Bluegill (*Lepomis macrochirus*): 0.223 - 0.46 mg/l 96 hours

**2- Propan-2-ol**

Ecotoxicity in water (LC50): 100000 mg/l 96 hours [Fathead Minnow]. 64000 mg/l 96 hours [Fathead Minnow].

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

### 13. Disposal Considerations

**Disposal method:**

Dispose of in accordance with federal, state, and local regulations.  
 US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**RCRA P-Series:** None listed.

**RCRA U-Series:** None listed.

### 14. Transport information

**Shipping Name:** Biostar classic 300

**Packing Group:** III

### 15. Other Information

**Safety, Health And Environmental Regulations/Legislation Specific For The Substance Or Mixture Authorizations or Restrictions (Regulation [EC] No 1907/2006, Title VII Respectively Title VIII):** Not applicable  
**Ingredients according to EC Detergents Regulation 648/2004**  
 Disinfectants

**Chemical safety assessment:** A chemical safety assessment has not been carried out on the mixture

**Full text of the R, H and EUH H225** Highly flammable liquid and vapour.

**phrases mentioned in section 3:** H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.



**German metal Surface treatment Chemicals Co.  
Research and Development Department.  
Detergent and disinfectants Division.**

## 16. Packing

**Packaging type:** HDPE containers and sealed cap.

**DISCLAIMER:** *The data contained herein are furnished for information only and are believed to be reliable. However, SUGEST and its affiliates ("SUGEST") do not assume responsibility for any results obtained by persons over whose methods SUGEST has no control. It is the user's responsibility to determine the suitability of SUGEST's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any SUGEST's products. In light of the foregoing, SUGEST specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SUGEST's products. SUGEST further disclaims any liability for consequential or incidental damages of any kind, including lost profits.*