



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

**Safety Data Sheet**

**According to 1907/2006/EC , Article 31**

**1 - Identification of the substance/preparation and of the company/undertaking**

**Product details**

· **Trade name:** **Dura Alkyd Primer**

· **Manufacturer/Supplier:**

German Surface treatment chemicals Co.

AL Fawzan industry Area

Riyadh

Saudi Arabia Kingdom

[amirqasqas@sugest.com.sa](mailto:amirqasqas@sugest.com.sa)

· **Further information obtainable from:** Product safety department

· **Information in case of emergency:** During normal opening times: +966 11 4647711

**2 - Hazards identification**

· **Hazard description:**



Xn Harmful

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 38 Irritating to skin.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.


**. (Contd. on page 2)**



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

· *GHS label elements*



**Warning**

H226 - Flammable liquid and vapour.



**Warning**

H332 - Harmful if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

· **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

· **Response:**

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

· **Disposal:**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.



· Trade name: **Dura Alkyd Primer**

### 3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with non-hazardous additions.

· ***Dangerous components:***

CAS: CAS 64742-82-1 EINECS: 265-185-4	<b>White spirit</b>	Xn R-65  Xi; R 10-20/21-38  Warning:  2.6/3;  3.1.D/4, 3.1.I/4, 3.2/2	20-35 %
--	---------------------	---	---------



· Trade name: **Dura Alkyd Primer**

#### **4 First aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

#### **5 - Fire-fighting measures**

· *Suitable extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder. Do not use water.*

· *For safety reasons unsuitable extinguishing agents: Water with full jet*

· *Protective equipment: Mouth respiratory protective device.*



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

**6 - Accidental release measures**

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

**7 - Handling and storage**

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.



· Trade name: **Dura Alkyd Primer**

## 8 - Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
78-83-1 butanol	
WEL	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm Long-term value: 154 mg/m <sup>3</sup> , 50 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 7)



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the Degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**





**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

### 9 - Physical and chemical properties

#### · General Information

**Form:** Fluid

**Colour:** According to product specification

**Odour:** Characteristic

#### · Change in condition

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 137°C

· **Flash point:** 30°C

· **Ignition temperature:** 500°C

· **Self-igniting:** Product is not self igniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### · Explosion limits:

**Lower:** 1.1 Vol %

**Upper:** 7.0 Vol %

· **Vapor pressure at 20°C:** 6.7 hPa

· **Density at 20°C:** 1.46 : 1.47 g/cm<sup>3</sup>

#### · Solubility in / Miscibility with

**water:** Not miscible or difficult to mix.

#### · Solvent content:

**Organic solvents:** 29,5 %





**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

### 10 - Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

### 11 - Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

**1330-20-7 xylene**

Oral	LD 50	4300 mg/kg (rat)
Dermal	LD 50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

### **12 - Ecological information**

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

### **13 - Disposal considerations**

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· Trade name: **Dura Alkyd Primer**

#### *14 Transport information*

· **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1993
- **Packaging group:** III
- **Hazard label:** 3
- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOBUTANOL (ISOBUTYL ALCOHOL))

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOBUTANOL



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· **Trade name: Dura Alkyd Primer**

· **UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S., 3, III**

### *15 Regulatory information*

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful

· **Hazard-determining components of labelling:**

xylene

· **Risk phrases:**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

· **Safety phrases:**

2 Keep out of the reach of children.

36/37 Wear suitable protective clothing and gloves.



**German metal Surface treatment Chemicals Co.  
Research and Development Department  
Paints Division.**

· **Trade name: Dura Alkyd Primer**

### *16 Other information*

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

37/38 Irritating to respiratory system and skin.

38 Irritating to skin.

41 Risk of serious damage to eyes.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department

· **Contact:** Mr. Taha Manzoor

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)