



## Safety Data Sheet

According to 1907/2006/EC , Article 31

### 1 - Identification of the substance/preparation and of the company/undertaking

#### Product details

· Trade name: **Dura Epoxy Primer**

· **Manufacturer/Supplier:**

German Surface treatment chemicals Co.

AL Fawzan industry Area

Riyadh

Saudi Arabia Kingdom

[Info@sugest.com.sa](mailto:Info@sugest.com.sa)

· **Further information obtainable from:** Product safety department

· **Information in case of emergency:** During normal opening times: +966 11 4647711

### 2 - Hazards identification

· **Hazard description:**



Xn Harmful

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 38 Irritating to skin.

· **Classification system:**


The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

. (Contd. on page 2)



· Trade name: **Dura Epoxy Primer**

· *GHS label elements*



**Warning**

H226 - Flammable liquid and vapour.



**Warning**

H332 - Harmful if inhaled.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

· **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

· **Response:**

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

· **Disposal:**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Dispose of contents/container in accordance with local/regional/national/international regulations.



· Trade name: **Dura Epoxy Primer**

### 3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· ***Dangerous components:***

CAS: 1330-20-7 EINECS: 215-535-7	xylene	Xn  Xi; R 10-20/21-38  Warning:  2.6/3;  3.1.D/4, 3.1.I/4, 3.2/2	20-35 %
CAS: 78-83-1 EINECS: 201-148-0	butanol	Xi; R 10-37/38-41-67  Danger:  3.3/1  Warning:  2.6/3;  3.8/3; 3.2/2	≤2.5 %

- **Additional information:** For the wording of the listed risk phrases refer to section 16.



· Trade name: **Dura Epoxy Primer**

#### 4 First aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

#### 5 - Fire-fighting measures

· *Suitable extinguishing agents: CO<sub>2</sub>, sand, extinguishing powder. Do not use water.*

· *For safety reasons unsuitable extinguishing agents: Water with full jet*

· *Protective equipment: Mouth respiratory protective device.*



· Trade name: **Dura Epoxy Primer**

### 6 - Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

### 7 - Handling and storage

Oil based Paints and Solvents are 'Hazardous Wastes' and as such are subject to much stricter regulations for storage and disposal than ordinary products / waste.

**We must ensure that the following rules are followed:**

- Paints and Solvents are to be stored in approved containers and areas on drip trays or banded pallets
- Containers are to be kept closed when not in use
- When transporting paints or solvents ensure the containers are closed.
- Ensure incompatible chemical products (those which may cause a hazardous reaction if they come in contact) are not stored together.
- Smoking is prohibited in flammable liquid storage areas.
- Flammable liquids are not to be stored near sources of ignition (sparks, electricity, flames or hot objects)
- When containers are empty they must be disposed of correctly, by a hazardous waste licensed carrier.
- All paints and solvent tins/containers should be clearly marked.
- Storing temperature not exceed more than 37 Celsius.
- The transportation trucks and vehicles must be covered well to isolate the coatings pails and tins from direct sunlight.
- The pails and tins must be stored in dry paces away from high humidity.



· Trade name: **Dura Epoxy Primer**

## 8 - Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

<b>1330-20-7 xylene</b>	
<i>WEL</i>	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
<b>78-83-1 butanol</b>	
<i>WEL</i>	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm Long-term value: 154 mg/m <sup>3</sup> , 50 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 7)



· Trade name: **Dura Epoxy Primer**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the Degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles



· Trade name: **Dura Epoxy Primer**

## 9 - Physical and chemical properties

### · General Information

**Form:** Fluid

**Colour:** According to product specification

**Odour:** Characteristic

### · Change in condition

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 137°C

· **Flash point:** 75°C

· **Ignition temperature:** 500°C

· **Self-igniting:** Product is not self igniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

### · Explosion limits:

**Lower:** 1.1 Vol %

**Upper:** 7.0 Vol %

· **Vapor pressure at 20°C:** 6.7 hPa

· **Density at 20°C:** 1.46 : 1.47 g/cm<sup>3</sup>

### · Solubility in / Miscibility with

**water:** Not miscible or difficult to mix.

### · Solvent content:

**Organic solvents:** 29.5 %

VOC (EC) : 29.5

**Solids content:** 76.5 %





· Trade name: **Dura Epoxy Primer**

### 10 - Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

### 11 - Toxicological information

· **Acute toxicity:**

· LD/LC50 values relevant for classification:		
<b>1330-20-7 xylene</b>		
Oral	LD 50	4300 mg/kg (rat)
Dermal	LD 50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful  
Irritant



· Trade name: **Dura Epoxy Primer**

## 12 - Ecological information

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

## 13 - Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.



· Trade name: **Dura Epoxy Primer**

### 14 Transport information

· Land transport ADR/RID (cross-border)



- ADR/RID class: 3 Flammable liquids.
- Danger code (Kemler): 30
- UN-Number: 1993
- Packaging group: III
- Hazard label: 3
- Description of goods: 1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOBUTANOL (ISOBUTYL ALCOHOL))

· Maritime transport IMDG:



- IMDG Class: 3
- UN Number: 1993
- Label 3
- Packaging group: III
- EMS Number: F-E,S-E
- Marine pollutant: No
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOBUTANOL (ISOBUTYL ALCOHOL))

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 3
- UN/ID Number: 1993
- Label 3
- Packaging group: III
- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (XYLENES, ISOBUTANOL (ISOBUTYL ALCOHOL))



· Trade name: **Dura Epoxy Primer**

· UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S., 3, III

### *15 Regulatory information*

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful

· **Hazard-determining components of labelling:**

xylene

· **Risk phrases:**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

· **Safety phrases:**

2 Keep out of the reach of children.

36/37 Wear suitable protective clothing and gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.



· Trade name: **Dura Epoxy Primer**

### *16 Other information*

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

37/38 Irritating to respiratory system and skin.

38 Irritating to skin.

41 Risk of serious damage to eyes.

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department

· **Contact:** Mr. Taha Manzoor

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent