



Material Safety Data Sheet

Duraclean 206

MANUFACTURER:

German Metal Surface Treatment Chemicals Co (SUGEST)

P.O. Box 2951,Riyadh 11461,K.S.A.

Tel: (00966) (011) 4647711 (20 Lines)

Fax: (00966) (011) 2170866

1. Product and Company Identification

NAME Duraclean 206
USE Used for cleaning, dust removing, degreasing for anodizing aluminum
LABEL Duraclean 206
Company German Metal Surface Treatment Chemicals Co.

2. Description:

Duraclean 206 is a potent powder degreaser especially formulated to clean Aluminum with highly deposits of polishing paste in dip process.

3. Chemical Composition

Ingredient	CAS No	Percent by weight
Sodium Borate Pentahydrate	12179- 04 – 3	1 – 20
Surfactant	Proprietary	3 - 10

4. Application

Duraclean 206 is the most suitable degreaser and cleaner for aluminum profiles and panels prior to Anodizing.

5. Physical & Chemical Properties

Appearance	Free flowing powder
Color	White
PH (1% sol.) at 25 °C	9.1 ±0.3
Total Alkaline Points (1%)	3.7±0.3
Foam Test (1%)	90 ± 20 ml



Material Safety Data Sheet

6. Hazards Identification

This product is an irritant to eye and skin (corrosive, Harmful)

Emergency Overview

Chemical material cause irritant to eye and skin at concentrated liquid

Potential Health Effects

Inhalation:

Harmful or fatal if swallowed.

Skin Contact:

Irritant will cause permanent skin damage, may cause sensitization by skin contact,

Eye Contact:

Causes irritation, and pain. Contact may cause tissue eye damage.

Chronic Exposure:

Chronic inhalation may cause serious problems the lungs.

7. First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention immediately.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Wash clothing before reuse, clean shoes before reuse. Get medical attention immediately.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.

8. Fire Fighting Measures

Fire:

This product is non – combustible

Explosion:

Not considered to be an explosion hazard at low concentration.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.(flood with water).

Special information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.



Material Safety Data Sheet

9. Accidental Release Measures

A- Release note:

Dilute with large volume of water.

B- Environmental precaution

Residual **Duraclean 206** are transferred to new empty bag for the second use under restricted condition.

10. Storage Information

Storage & Handling	Keep bags tightly closed. Keep bags in a cool, well-ventilated area. Do not expose to direct sun. Stable nonflammable product. Avoid store near acids , alcoholic, reducing materials Store in temperature not above 40°C. Observe all warnings and precautions listed for the product. Duraclean 206 is stored only in polypropylene lined bags and transferred only in a prescribed manner and never return unused Duraclean 206 to original bag.
Shelf Life	Two years from date of production if stored in normal condition.

11. Exposure Controls/Personal Protection

Exposure control avoid eye and skin contact.

Personal protection wears gloves, goggles and overalls when handling the material.

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, a Manual of Recommended Practices*, most recent edition, for details.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. (Neoprene, polyvinyl chloride).

Eye Protection:

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

12. Stability and Reactivity

Stability:

stable at normal condition.

Reactivity Data

STABILITY: Stable under normal conditions

Hazardous Polymerization: will not occur

Avoid mix with acid.



Material Safety Data Sheet

13. Disposal Considerations

Disposal method: Undiluted product is regulated under environmental and transportation laws as corrosive and harmful. Disposal according to all laws, local and global authorities for restrictions on disposal of chemical waste ,manage chemical, waste through an approved waste treatment facility , do not reuse empty container ,rinse empty container with water before discarding container in accordance with current local community codes please recycle empty container whenever possible.

14. Transport information

Non hazardous.

15. Other Information

Label Hazard Warning:

WARNING! HARMFUL IF SWALLOWED OR INHALED.

Label Precautions:

Avoid contact with eyes, skin and clothing.
Avoid breathing fume.
Keep container closed.
Use only with adequate ventilation.
Wash thoroughly after handling.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel. Give milk or water. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, wipe off excess material from skin then immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases, get medical attention.

16. Packing Type:

Duraclean 206 is packed in Woven polypropylene lined bags.

Duraclean 206 is available in 25 kg bag.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.